

CJV23系列 series











汽車產品、 分析檢測、 水迴圈處理、 廚房衛浴、 美容美體等

Application: Household appliance,

Automobile,

Detection and analysis, Water recycling treatment, Kitchen and bathroom,

Cosmetology and bodycare etc.



産品參數表 Parameters									
型號 Model	額定電壓 Rated voltage	額定電流 Rated current	直流阻抗 DC resistance	負載流量 (氣體, 6psi) Flow under load	氣密性 Leakage	最低工作電壓 Min operating voltage	介質 Medium	工作模式 Type	
CJV23-C12A1	DC 12 V	< 110 mA	114 Ω±5%	> 11 L/min	< 1 CC/min	< 10 V	清水、水蒸氣 Clean water, vapor	隔膜式常閉 Normal close	
CJV23-C24A1	DC 24 V	< 68 mA	370 Ω±5%	> 11 L/min	< 1 CC/min	< 21.5 V	清水、水蒸氣 Clean water, vapor	隔膜式常閉 Normal close	
其它參數 Others									
壽命實驗 Life	test		120,00	120,000次 (負載362mmHg,閉合30秒排氣10秒爲一個循環)					
使用環境 Wo	rking envir	onment	0~50°	0~50°C, 75%RH					
业 产日准组层	今塚田 市 1	il Mila in.	ontion note						

此産品獲得國家發明專利。 With invention patent.

產品特點:常開閥,具有良好的密封性及耐介質腐蝕性。 Feature: Normal Close, premium anti-corrosion and sealing performance.

可根據客户具體要求進行定制。Customization based on specific customer requirements available.



